








REV.	ECH NO	LOCATIONS	DESCRIPTION	DATE



- Note:
- Material:
 - Housing: High temperature thermoplastic with g.f, UL94V-0
 - Contact: copper alloy, t=0.15mm
 - Shell: copper alloy, t=0.25mm
2. Specification:
- Current rating: 1 A Max. voltage: 100 V(ac) for 1 min.
 - Contact resistance: 50 mW Max.
 - Insulation resistance: 100 MW Min.
 - Total mating force: 3.57 Kgf Max.
 - Total unmating force: 1.0 Kgf Min. 0.81~2.05 Kgf Min.
 - Temperature range: -30°C~80°C

A 01 S B 1 4 1 B 3-329

- 产品代号 A: 部品
- 产品系列 01: micro usb 5p in
- 产品类别 S: 母座
- 产品类型 B: B TYPE
- 外壳材料 1: 2980R-H
- 端子材料 4: 5181R-BH
- 主体材质 1: LCP
- 主体颜色 B: 黑色
- 下板类型 3: 沉板式
- 细节流水 238: micro usb 5p B Type SMT脚位数: 6脚内插式板数

PART NO:	A01SB141B3-329	MATERIAL:	SEE NOTE
MODEL NO:	XX	FINSH:	SEE NOTE
UNIT:	MM	SIZE:	A4
TOLERANCE UNSPECIFIED	.x	DR:	xiayoulong
	.xxx	CHK:	
	.xxx	APP:	
	Ang.		

TITLE:		SCALE:	DATE:
Micro usb 5s B Type SMT脚位数: 6脚只脚无翻边		5:1	2012.05.04
DWG NO:	SHK-20038	REV:	A

深圳市虹康科技有限公司

