



规格说明: Specifications:
电气特性: Electrical:

- 1 额定电流: Current Rating: 5A/Contact terminal
- 2 额定电压: Voltage Rating: 30V DC
- 3 接触阻抗: Contact Resistance: 30 milliohms MAX
- 4 耐压: Dielectric Withstanding Voltage: 500 V AC AT Sea Level
- 5 绝缘阻抗: Insulation Resistance: 1000MEGA ohms MIN

物理性能: Mechanical:

- 1 插拔力: Contact Mating Force: 357kgf(MIN) / 302kgf(MAX)
- 2 端子保持力: Terminal Retention: 2kgf(MIN)

原材料: Material:

- 1 塑胶: Housing: High Temperature Thermoplastics, UL 94V 0 PBT White/Black
- 2 端子: Contact: Copper Alloy C2680
- 3 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

- 1 端子: Contact: Plated Gold High Mathing Area; Thickness: 10um
- 2 外壳: Shell: Nickel Plating

PCB LAY-OUT
(BOTTOM VIEW)



深圳市虹康科技有限公司

品名 (ITEM NO)	
料号 (PART NO)	SHK-20084
模号 (MODEL NO)	A008-1I

图号 (DWG NO)		单位 (UNIT):	MM
版本 (REV)	A/0	比例 (SCALE)	1:1
日期 (DATE)		公差	未注公差
设计 (DESIGN)		TOLERANCE UNSPECIFIED	
审核 (CHECKED)		X.X	±0.30
核准 (APPROVED)		X.XX	±0.20
		X.XXX	±0.10
		X°	±5°
		X.X°	±2°