







REV	LTR	DESCRIPTION	DATE	APPROVED
A0		依新料号编码原则发行图面		



RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

- SPECIFICATION:
- CURRENT RATING: 1.5A MAX
 - VOLTAGE: 100 VAC
 - TEMPERATURE RANGE: -30 °C ~ 85 °C
 - CONTACT RESISTANCE: 40 MILLIONHM MAX
 - INSULATION RESISTANCE: 100 MEGOHMS MIN.
 - INSERTION FORCE : 5N~20N
 - UNMATING FORCE: 8N~20N
 - DURABILITY: 10,000 CYCLES



A1	GND	B12	GND
A2	SSTXP1	B11	SSRXP1
A3	SSTXN1	B10	SSRXN1
A4	VBUS	B9	VBUS
A5	CCI	B8	SBU2
A6	DP1	B7	DN2
A7	DN1	B6	DP2
A8	SBU1	B5	CC2
A9	VBUS	B4	VBUS
A10	SSRXN2	B3	SSTXN2
A11	SSRXP2	B2	SSTXP2
A12	GND	B1	GND
PIN	SIGNAL NAME	PIN	SIGNAL NAME

TOLERANCES
 .I ±0.38
 .II ±0.25
 .III ±0.10
 ANGLES ±3.00°

TITLE: 5
 USB TYPE C/快充沉板0.8 无弹
 PART NO.: SHK-31003

深圳市虹康科技有限公司

DRAWING NO.: 812039-070

APPR.:	SCALE:	SHEET:
CHECK:	1:1	1/1
DRAWN:	UNIT: M M	
REV.:	SIZE: A4	
A/0		

