



P.C.B LAYOUT

规格说明: Specifications:
电气特性: Electrical:

- 额定电流: Current Rating**
1.5A/contact terminal
- 额定电压: Voltage Rating**
30V DC
- 接触阻抗: Contact Resistance**
30 milliohms MAX
- 耐电压: Dielectric Withstanding Voltage:**
500 V AC AT Sea Level
- 绝缘阻抗: Insulation Resistance:**
1000MEGA ohms MIN

物理性能: Mechanical:

- 插拔力: Connector Mate and Unmate Force**
Mate force: 3.57kgf (MAX)
Unmate force: 1.02kgf (MIN)
- 端子保持力: Terminal Retention**
1.2kgf (MIN)

原材料: Material:

- 塑胶: Housing:**
Hing Temperature Thermoplastics,
UI 94V-0 PBT White/Black
- 端子: Contact: Copper Alloy C2680**
- 外壳: Shell: Copper Alloy C2680/SPCC**

电镀: Finish:

- 端子: Contact: Plated Gold in Mating Area;**
Tin On Solder Tails
- 外壳: Shell:**
Nickel Plating



深圳市虹康科技有限公司

品名 (ITEM NO)	AF10.0侧插短体卷边
料号 (PART NO)	SHK-20082
模号 (MODEL NO)	A008-1I-4
图号 (DWG NO)	
版本 (REV)	
日期 (DATE)	
设计 (DESIGN)	
审核 (CHECKED)	
核准 (APPROVED)	

单位 (UNIT):	MM
比例 (SCALE):	1:1
公差	未注公差
TOLERANCE UNSPECIFIED	
X.X	±0.30
X.XX	±0.20
X.XXX	±0.10
X°	±5°
X.X°	±2°