

规格说明:Specifications:

电气特性:Electrical:






- 1. 额定电流: Current Rating
1.5A/contact terminal
- 2. 额定电压: Voltage Rating
30V DC
- 3. 接触阻抗: Contact Resistance
30 milliohms MAX
- 4. 耐电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 5. 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:


- 1. 插拔力: Cnnector Mate and Unmate Force
Mate force: 3.57kgf (MAX)
Unmate force: 1.02kgf (MIN)
- 2. 端子保持力: Terminal Retention
1.2kgf (MIN)

原材料: Matorial:

- 1. 塑胶: Housing:
Hing Temperature Thermoplastics,
U1 94V-0 PBT White/Black
 - 2. 端子: Contact: Copper Alloy C2680
 - 3. 外壳: Shell: Copper Alloy C2680/SPCC
- 电镀: Finish:
- 1. 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
 - 2. 外壳: Shell:
Nickel Plating



P.C.B LAYOUT



深圳市虹康科技有限公司

品名 (ITEM NO)	AF10.0侧插短体平口	图号 (DWG NO)		单位 (UNIT): MM
料号 (PART NO)	SHK-20082	版本 (REV)		比例 (SCALE) 1:1
模号 (MODEL NO)	A008-11-4	日期 (DATE)		
		设计 (DESIGN)		未注公差
		审核 (CHECKED)		TOLERANCE UNSPECIFIED
		核准 (APPROVED)		X.X ±0.30 X.XX ±0.20 X.XXX ±0.10 X.X° ±5° X.X° ±2°