

规格说明:Specifications:

电气特性:Electrical:




1. 额定电流: Current Rating
1.5A/contact terminal
2. 额定电压: Voltage Rating
30V DC
3. 接触阻抗:Contact Resistance
30 milliohms MAX
4. 耐电压:Dielectric Withstanding Voitage:
500 V AC AT Sea Level
5. 绝缘阻抗:Insulation Resistance:
1000MEGA ohms MIN

物理性能:Mechanical:

1. 插拔力: Cnnector Mate and Unmate Force
Mate force:3.57kgf(MAX)
Unmate force:1.02kgf(MIN)
2. 端子保持力: Terminal Retention
1.2kgf(MIN)

原材料:Matorial:

1. 塑胶:Housing:
Hing Temperature Thernaplastics,
UL 94V-0 PBT White/Black
2. 端子>Contact:Copper Alloy C2680
3. 外壳:Shell: Copper Alloy C2680/SPCC
- 电镀:Finish:
1. 端子>Contact: Piated Gold in Mating Area;
Tin On Solder Talls
2. 外壳:Shell:
Nickel Plating



RECOMMENDED P.C.B LAYOUT

深圳市虹康科技有限公司

品名 (ITEM NO)
A/F 壳体10.0全贴卷边6.8

料号 (PART NO)
SHK-0098

模号 (MODEL NO)

图号 (DWG NO)	单位 (UNIT) : MM
版本 (REV)	比例 (SCALE) 1:1
日期 (DATE)	
设计 (DESIGN)	
审核 (CHECKED)	
核准 (APPROVED)	

公差	未注公差
X.X	TOLERANCE UNSPECIFIED
X.XX	±0.30
X.XXX	±0.20
X°	±0.10
X'°	±5°
X''°	±2°