

Max	Modification	Date	Draw	Approve
A				

规格说明:Specifications:

电气特性:Electrical:

- 额定电流: Current Rating
1.5A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触电阻: Contact Resistance
30 milliohms MAX
- 耐压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 绝缘电阻: Insulation Resistance:
1000MEGA ohms MIN

物理性能:Mechanical:

- 插拔力: Connector Mate and Unmate Force
Mate force:3.57kgf(MAX)
Unmate force:1.02kgf(MIN)
- 端子保持力: Terminal Retention
1.0kgf(MIN)

原材料:Material:

- 塑胶: Housing:
Hing Temperature Ternmaplastics,

电镀:Finish:

- 端子: Contact: Copper Alloy C2680
- 外壳: Shell: Copper Alloy C2680/SPCC
- 端子四周镀50U"(MIN)锡,镀金区域镀100-200U"镀金1U"
- 外壳: Shell:
铜壳四周镀80U"(MIN)锡

Nickel Plating



深圳市虹康科技有限公司

成品图		MANUFACTURE DWG	
公差一覽表			
TOLERANCE UNLESS OTHERWISE			
.X±0.15	X.±5°	日期 DATE	單位 UNIT
XX±0.05	.X±2°	核校 CHECKED	製圖 DRAWING
XXX±0.02	.XX±1°	核准 APPROVE	審核外校
		APPROVE	NAME
		NEW	VER
		SHK-20100	VER
			PG1