



PCB.LAYOUT

- 91-US01-XXX
- 189: PBT白色, 端子镀半金1u", 铜壳
 - 190: PBT白色, 端子镀半金1u", 铁壳
 - 191: PBT黑色, 端子镀半金1u", 铜壳
 - 192: PBT黑色, 端子镀半金1u", 铁壳

电镀:
端子: 接触区域镀金1u", 焊接区镀亮锡100-200u"
外壳: 全区域镀镍50-80u"

材料:
胶芯: PBT
端子: 黄铜C2680
外壳: 黄铜C2680/SPCC

说明:
电气性能:
接触阻抗: 30毫欧 (最大)
绝缘阻抗: 1000兆欧 (最小)
耐高压: 500V AC 一分钟

TOLERANCE UNLESS OTHERWISE SPECIFIED

XXX	±0.10
XX	±0.20
X	±0.30
∅	±.3

REV:	DESCRIPTION	REV BY	APPROVED	DATE	MATL:	SEE SPECIFICATION	APPROVED

PROJECTION:	THIRD ANGLE PROJECTION	CHECKED		
UNIT:	SCALE	REV(NO)	SHEET	DRAWN
mm	1:1	A	1 OF 1	DATE
				2011.06.08

产品名称	USB AF 180°直插弯脚13.0
PART NAME:	
料号	SHK-20072
PART No:	

深圳市虹康科技有限公司