



Recommended P. C. B. Layout
Thickness: 1.6 MIN

NOTES:
 1. MATERIAL:
 1.1 HOUSING: PBT BK;
 1.2 CONTACTS: COPPER ALLOY;
 1.3 SHELL: STEEL ALLOY.
 2. FINISHED:
 SHELL: 50u" MIN Ni UNDER PLATED OVER ALL;
 CONTACTS: GOLD FLASH ON CONTACT AREA
 Tin 80u" MIN ON SOLDER AREA.
SPECIFICATIONS:
 Contact current Rating: 1Amperes.
 DIELECTRIC Withstanding Voltage: AC 500V.
 Insulation resistance: 1000M Ω Minimum.
 Contact Resistance: 30m Ω Maximum.
 Operating Temperature: -30 $^{\circ}$ C to +85 $^{\circ}$ C.



图面流行	变更说明	姓名	时间	审核	时间	一般公差 GENERAL TOL. X \pm 0.3 XX \pm 0.2 XXX \pm 0.1 XXX \pm 0.05	制图 DRAWN	Y X	产品编号 PRODUCT NO. SHK-20075	图号 DWG NO.	张数 SHEET	单位 UNIT	比例 SCALE
审核 REV	审核 REVISION	审核 SIGN	审核 DATE	审核 CHECKED	审核 DATE	检查 CHECKED	检查 APPROVAL	角注 PROJ.			产品名称 PRODUCT NAME USB-A 插板长体17.5弯角	深圳市虹康科技有限公司	mm