



Recommended P. C. B. Layout
Thickness: 1.6 MIN

NOTES:

1. MATERIAL:
 - 1.1 HOUSING: PBT BK;
 - 1.2 CONTACTS: COPPER ALLOY ;
 - 1.3 SHELL: STEEL ALLOY .
2. FINISHED:
 - SHELL: 50 μ MIN Ni UNDER PLATED OVER ALL;
 - CONTACTS: GOLD FLASH ON CONTACT AREA
 - Tin 80 μ MIN ON SOLDER AREA.

SPECIFICATIONS:

Contact current Rating: 1ampere.
 DIELECTRIC Withstanding Voltage: AC 500V.
 Insulation resistance: 1000M Ω Minimum.
 Contact Resistance: 30m Ω Maximum.
 operating Temperature: -30°C to +85°C.

<p>图面发行</p> <p>变更说明 MODIFICATION</p>	<p>Y X</p> <p>2015.9.28</p> <p>审签 SIGN</p> <p>审核 CHECKED</p> <p>时间 DATE</p>	<p>一般公差 GENERAL TOL.</p> <p>X ± 0.3</p> <p>XX ± 0.2</p> <p>X ± 0.05</p> <p>XX ± 0.02</p>	<p>制图 DRAWN</p> <p>审核 CHECKED</p> <p>批准 APPROVAL</p> <p>角注 PROL.</p> <p>Y X</p>	<p>产品名称 PRODUCT NAME</p> <p>USB-A插板长体20.5弯脚</p>	<p>图号 DWG NO</p> <p>SHK-20076</p> <p>数量 SHEET</p> <p>单位 UNIT</p> <p>比例 SCALE</p>	
<p>深圳市虹康科技有限公司</p> <p>SHENZHEN HONGKANG TECHNOLOGY CO., LTD.</p>						