



PCB LAYOUT

规格说明: Specifications:

电气特性: Electrical:

- 1. 额定电流: Current Rating
1.5A/contact terminal
- 2. 额定电压: Voltage Rating
30V DC
- 3. 接触阻抗: Contact Resistance
30 milliohms MAX
- 4. 耐电压: Dielectric Withstanding Voltage:
500 V AC At Sea Level
- 5. 绝缘阻抗: Insulation Resistance:
1000MΩGA ohms MIN

物理性能: Mechanical:

- 1. 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf (MAX)
Unmate force: 1.02kgf (MIN)
- 2. 端子保持力: Terminal Retention
1.2kgf (MIN)

原材料: Material:

- 1. 塑胶: Housing:
Hing Temperature Thermoplastics,
UI 94V-0 PBT White/Black
- 2. 端子: Contact: Copper Alloy C2680
- 3. 外壳: Shell: Copper Alloy C2680/SPCC

- 电镀: Finish:
- 1. 端子: Contact: Plated Gold in Mating Area:
Tin On Solder Tails
 - 2. 外壳: Shell:
Nickel Plating

深圳市虹康科技有限公司	
品名 (ITEM NO)	USB A 180 度 22.5 度 宽 口 直 脚
料号 (PART NO)	SHK-20077
模号 (MODEL NO)	

图号 (DWG NO)		单位 (UNIT): MM
版本 (REV)	A/0	比例 (SCALE) 1:1
日期 (DATE)	2016.06.08	未注公差 F1: ±0.30 F2: ±0.20 F3: ±0.15 F4: ±0.10 F5: ±0.05
设计 (DESIGN)		审核 (CHECKED)
审核 (CHECKED)		批准 (APPROVED)