



ITEM:	REVISION	REV BY	APPROVED	DATE	MATL:	SEE SPECIFICATION	APPROVED
					PROJECTION:	THIRD ANGLE PROJECTION	CHECKED
					UNIT:	SCALE	DRAWN
					mm	1:1	DATE

TOLERANCE UNLESS OTHERWISE SPECIFIED
XXX ±0.10
XX ±0.20
X ±0.30
.X ±.5

产品名称	USB 3.0AAF双层180度
PART NAME:	
料号	SHK-30135

SPECIFICATIONS:
 Contact current Rating:
 1.8 Amperes for pin1&pin4.
 0.25 Amperes other contacts
 Dielectric Withstanding Voltage:AC 100V(RMS)
 Insulation resistance:100Megohms Minimum.
 Contact Resistance:
 30mΩ Max for other contacts
 50mΩMax for other contacts
Mechanical Characteristics:
 Mating Force:35 Newtons,Maximum
 Unmating Force:10 Newtons,Minimum.
MATERIAL:
 Housing: PBT+30%GF 94Y-0 COLOR:BLUE
 Contact: copper alloy(T=0.25mm)
PLATING:
 Shell: Nickel Plated
 Contact: Au Plated on contact area
 Tin Plated on solder area
 Nickel underplating over all
 operating Temperature:-55°to+85°

9	8	7	6	5	4	3	2	1
---	---	---	---	---	---	---	---	---

深圳市虹康科技有限公司
 90607161