



RECOMMENDED PCB LAYOUT

- NOTES:
- MATERIAL:
 - HOUSING: LCP UL94V-0 BLUE
 - CONTACT: 1~4PIN,COPPER(T=0.20mm) 5~9PIN,BRASS(T=0.20mm)
 - SHELL: FRONT SHELL,BRASS(T=0.30mm) COVER SHELL,SPCC(T=0.20mm)
 - ELECTRICAL CHARACTERISTICS:
 - CONTACT RESISTANCE:30mΩ MAX.
 - CONTACT CURRENT RATING:1.5A
 - DIELECTRIC WITHSTANDING VOLTAGE:500 V R.M.S.
 - INSULATION RESISTANCE 1000 MEGOHMS MIN.
 - OPERATING TEMPERATURE:-40°C~85°C
 - MECHANICAL CHARACTERISTICS:
 - MATING FORCE:3.57kg MAX.
 - UNMATING FORCE:1.02kg MIN.
 - DURABILITY:MANDATORY:5000 CYCLES.
 - PLATING
 - TERMINAL:GOLD FLASH ALL OVER 40U"MIN, NICKEL AND 10U"MIN TIN ALL OVER 40 U"MIN.
 - SHELL: 40 U" MIN,NICEL OVER 40U"MIN BRASS.

REV:	DESCRIPTION	REV BY	APPROVED	DATE	MATL:	SEE SPECIFICATION	THIRD ANGLE PROJECTION	APPROVED

产品名称	USB BF 3.0 DIP
PART NAME:	
料号	SHK-30438
PART No:	

C

PROJECTION:	UNIT:	SCALE	REV(NO)	SHEET	DRAWN	DATE
	mm	1:1	A	1 OF 1		2011.10.06

深圳市虹康科技有限公司