

项目 Mdx	变更内容 Modification	日期 Date	修改人 Draw	核准 Approve

规格说明: Specifications:
电气特性: Electrical:

- 额定电流: Current Rating
3.1A/contact terminal
- 额定电压: Voltage Rating
30V DC
- 接触阻抗: Contact Resistance
30 milliohms MAX
- 绝缘电压: Dielectric Withstanding Voltage:
500 V AC AT Sea Level
- 绝缘阻抗: Insulation Resistance:
1000MEGA ohms MIN

物理性能: Mechanical:

- 插拔力: Connector Mate and Unmate Force
Mate force: 3.57kgf(MAX)
Unmate force: 1.02kgf(MIN)
- 端子保持力: Terminal Retention
1.0kgf(MIN)

原材料: Material:

- 塑壳: Housing:
Hing Temperature Thermoplastics,
- 端子: Contact: Copper Alloy C2680
- 外壳: Shell: Copper Alloy C2680/SPCC

电镀: Finish:

- 端子: Contact: Plated Gold in Mating Area;
Tin On Solder Tails
- 外壳: Shell:
铜壳四周镀80U”(MIN)镍



Nickel Plating

深圳市虹康科技有限公司

成品图 MANUFACTURE DWG	公差 TOLERANCE UNLESS OTHERWISE SPECIFIED	日期 DATE	单位 UNIT	比例 SCALE	图号 DRAWING NO.	姓名 NAME	版本 VER	页码 SHEET
	X±0.20	2016.10.20	MM	1:1	231060	沈振	A0	009
	X±0.10							
	XXX±0.02 .XX±1"							

